City of Columbia City Lot Coverage Calculation EXAMPLE

<u>10,000</u> sq. ft. lot square footage
2,450 sq. ft. principal structure footprint
<u>140</u> sq. ft. additional structure(s) footprint
<u>680</u> sq. ft. driveway(s)
0 sq. ft. additional paving (include: walkways, patios etc.)
Total square feet of coverage ÷ lot square footage = % of lot coverage.
Lot Coverage %: <u>33%</u>

Zone	Maximum lot coverage %
R-1 & R-2	50%
R-3	70%
MHP	80%

Chapters 7.40 (R-1) Low Density Residential Zone and 7.45 (R-2) Moderate Density Residential Zone of Columbia City's Development Code reads: *Buildings, portable storage structures and paving shall not occupy more than 50% of the lot or parcel.*

Chapter 7.50 (R-3) High Density Residential Zone of Columbia City's Development Code reads: Buildings, portable storage structures and impervious surfaces shall not occupy more than 70% of the lot or parcel. No single building shall contain more that four dwelling units. Buildings shall have a separation of 12 feet from all adjacent buildings, except single family attached townhouse at the common property line.

Chapter 7.55 (MHP) Manufactured Home Park Zone of Columbia City's Development Code reads: *Imperious surfaces shall not cover more than 80% of the lot or parcel.*

Created 5/3/18